

10/518511

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
8 January 2004 (08.01.2004)

PCT

(10) International Publication Number
WO 2004/002774 A1

(51) International Patent Classification⁷: B60N 2/42, 2/427

(74) Agent: UNITECTRA; Möhrlistrasse 23, CH-8006 Zürich (CH).

(21) International Application Number:

PCT/EP2003/006615

(22) International Filing Date: 24 June 2003 (24.06.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02405537.8 26 June 2002 (26.06.2002) EP

(71) Applicants (for all designated States except US): UNIVERSITY OF ZÜRICH [CH/CH]; Office Vice President of Research, Rämistrasse 71, CH-8006 Zürich (CH). ETH Zürich ETH TRANSFER [CH/CH]; Raemistrasse 101, CH-8092 Zürich (CH).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventors; and


(75) Inventors/Applicants (for US only): MUSER, Markus [CH/CH]; Seestrasse 79, CH-8820 Wädenswil (CH). SCHMITT, Kai-Uwe [DE/CH]; Bucheggstrasse 160, CH-8057 Zürich (CH).

Published:

— with international search report

[Continued on next page]

(54) Title: SEAT COMPONENT TO PREVENT WHIPLASH INJURY



(57) Abstract: A seat component to prevent whiplash injury during a rapid motion change of a vehicle comprises means allowing a displacement of the seat and a person sitting thereon backwards (22) in relation to the direction of movement at the motion change. These means comprise a body (11, 18) to be affixed to or being part of the seat, a slide element (16) affixed to the vehicle and being in guiding contact with said body to guide a translational displacement of the seat over a predetermined distance. It further comprises a trigger system (13) to detect a acceleration threshold, a release mechanism (14) controlled through the trigger system (13) to enable said translational displacement (22) and a damping component (17) to damp said translational displacement (22). The trigger system (13) opens the release mechanism (14) only upon detection of an acceleration value above a predetermined threshold. The NIC experienced when using a conventional seat can be reduced by 40% if said seat is equipped with the device according to the invention.

WO 2004/002774 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.